

## HENAN BEBON INTERNATIONAL CO.,LTD.

Address: 33HEX BUILDING, ENTERPRISES HEADQUARTERS BASE, NATIONAL HIGH-TECH INDUSTRIAL DEVELOPMENT ZONE ZHENGZHOU, CHINA



Email: [bb@bebonchina.com](mailto:bb@bebonchina.com) Mobile: +86-15737657202

Phone: +86-371-86151627 Fax: +86-371-86011881

Upgrading Our Brand Image from BEBON to BBN

Web: [www.bebonchina.com](http://www.bebonchina.com), [www.steel-plate-sheet.com](http://www.steel-plate-sheet.com)

TYPE	OD (mm)	SCH40		SCH80		SCH160	
		Wall Thick (mm)	US \$/ton EXW	Wall Thick	US\$/ton EXW	Wall Thick(m)	US\$/ton EXW
1/2"	21.3	2.77	808.76	3.73	808.76	4.78	808.76
3/4"	26.7	2.87	750.36	3.91	750.36	5.56	750.36
1"	33.4	3.38	670.07	4.55	670.07	6.35	670.07
1.1/4"	42.2	3.56	633.58	4.85	633.58	6.35	633.58
1.1/2"	48.3	3.68	626.28	5.08	626.28	7.14	626.28
2"	60.3	3.91	626.28	5.54	626.28		
2.1/2"	73.0	5.16	620.44	7.01	620.44		
3"	88.9	5.49	620.44	7.62	620.44		
1"	33.4	3.38	490.69	4.55	490.69	6.35	538.34
1-1/4"	42.2	3.56	450.98	4.85	450.98	6.35	466.87
1-1/2"	48.3	3.68	443.04	5.08	443.04	7.14	474.81
2"	60.3	3.91	435.1	5.54	435.1	8.74	450.98
2-1/2"	73	5.16	30.08	7.01	435.1	9.53	466.87
3"	88.9	5.49	427.16	7.62	427.16	11.13	466.87
4"	114.3	6.02	427.16	8.56	427.16		
5"	141.3	6.55	439.87	9.53	439.87		
6"	168.3	7.11	419.22	10.97	419.22		
8"	219.1	8.18	30.08	12.7	419.22		
10"	273	9.27	419.22	15.09	419.22		
12"	323.8	10.31	423.98	17.48	423.98		
14"	355.6	11.13	439.87	19.05	439.87		
16"	406.4	12.7	447.81	21.44	447.81		
18"	457.2	14.27	463.69	23.83	463.69		
20"	508	15.09	490.69	26.19	506.58		
24"	609.6	17.48	506.58	30.96	522.46		

Above price is for black seamless pipe

Grade: ASTM A106/A53 GRB

Length: 5800mm, 6000mm

Thickness: SCH10, SCH20, SCH30, SCH40, SCH60, SCH80, SCH100, SCH120, SCH140, S

For Galvanized pipe price, please sent inquiry details to us

Grade	OD (mm)	Wall Thick (mm)	US \$/ton EXW
API 5L API 5L A106GRB	33.4	3.38	703.65
API 5L	33.4	4.55	703.65
API 5L	33.4	6.35	703.65
API 5L	42.2	3.56	667.15

API 5L	42.2	4.85	667.15
API 5L	42.2	6.35	667.15
API 5L	48.3	3.68	659.86
API 5L	48.3	5.08	659.86
API 5L	48.3	7.14	659.86
API 5L	60.3	3.91	659.86
API 5L	60.3	5.54	659.86
API 5L	73.0	5.16	652.55
API 5L	73.0	7.01	652.55
API 5L	88.9	5.49	652.55
API 5L	88.9	7.62	652.55

Sizing: 5.8/6M

Standard:GB/T8163-2008